

PSEN op2H-s-30-045/1

630722












Technical details

Product version:	1.0
Approvals:	CE;cULus Listed;TÜV
Sensor principle:	Optical
Type in accordance with EC 61496:	Type 2
Number of beams:	24
Height of protected field:	450 mm
Resolution of safety device:	30 mm
Operating range (m):	0,2 - 19,0
Reaction time:	11.00 ms
Number of OSSD outputs:	2
Muting:	No
Blanking:	No
Supply voltage (V):	24,0
Supply voltage type:	DC
Application in accordance with:	CLC/TS 61496-2;EN 61496-1
Protection type, housing:	IP65
Resolution, protection type:	Hand
Width dimension:	32.3 mm
Height dimension:	533.2 mm
Depth dimension:	36.9 mm

Gross weight:	2500 g
Net weight:	2000 g
Ambient temperature:	0 - 55 °C

Accessories

	630297	PSEN op cable axial M12 5-pole 30m
	630303	PSEN op cable axial M12 4-p. shield. 3m
	630304	PSEN op cable axial M12 4-p. shield. 5m
	630305	PSEN op cable axial M12 4-p. shield. 10m
	630306	PSEN op cable angle M12 4-p. shield. 3m
	630307	PSEN op cable angle M12 4-p. shield. 5m
	630308	PSEN op cable angle M12 4-p. shield. 10m

	630309	PSEN op cable axial M12 4-p. shield. 30m
	630310	PSEN op cable axial M12 5-pole 3m
	630311	PSEN op cable axial M12 5-pole 5m
	630312	PSEN op cable axial M12 5-pole 10m
	630319	PSEN op cable angle M12 4-p. shield. 30m
	630347	PSEN op cable angle M12 5-pole 3m
	630348	PSEN op cable angle M12 5-pole 5m
	630349	PSEN op cable angle M12 5-pole 10m
	630350	PSEN op cable angle M12 5-pole 30m



630298

PSEN cable M12-5sf 20m



630365

PSEN op cable angle M12 5-pole 50m



630364

PSEN op cable axial M12 5-pole 50m