



## Technical details

|   |   |
|---|---|
| Product version:                        | 3.7   |
| Approvals:                              | CE;cULus Listed;TÜV;CCC   |
| Application options:                    | Safety gate monitor;Instantaneous E-STOP monitoring;Limit switch;Light beam device mon. Type 4;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 2 with t/p   |
| Operating modes:                        | Single-channel;Automatic reset;Dual-channel;Detection of shorts across contacts;Start-up testing;Monitored manual reset;without detection of shorts across contacts;Self test |
| Product standard:                       | EN 60947-5-1  |
| Standards:                              | DIN V VDE 801-1/A1;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1;VDE 0116   |
| Supply voltage (V):                     | 24,0  |
| Supply voltage type:                    | DC  |
| Terminal type:                          | Screw terminal  |
| Terminal style:                         | Plug-in   |
| Number of instantaneous safety outputs: | 2 ST  |
| Number of test pulse outputs:           | 2   |
| Stop category:                          | 0   |
| Width dimension:                        | 22.5 mm   |
| Height dimension:                       | 94.0 mm   |
| Depth dimension:                        | 121.0 mm  |
| Gross weight:                           | 140 g   |
| Net weight:                             | 120 g   |

Ambient temperature:

-10 - 55 °C

## Related Products



374280

PNOZ X Set plug in screw terminals P1+P2



774195

Terminal block filter 1



774196

Terminal block filter 2

874130B

PNOZelog Driver CD