

## 14.6 Metaloxide (ZnO) Varistors

Types	$V_V$ max.	$V_{DC}$ max.	$V_{DC} \pm 10\%$ ( $I_{DC} = 1\text{ mA}$ )	$\hat{I}_p^{1,2)}$ max. repetitive	$\hat{I}_p^{1,3)}$ max. non-repetitive	$\hat{W}_p^{1,3)}$ max.	$\hat{P}_{AV}$ max. $T_{amb} \leq 70\text{ °C}$	$\hat{V}_{pmax}(\hat{I}_p^1) = \dots$			w g
	V	V	V	A	A	J	W	(10 A) V	(100 A) V	(1000 A) V	
<b>Wire terminals <sup>4)</sup></b>											
SKVA 14 A 42	42	56	68	150	4500	24,6	0,6	110	130	215	3
SKVA 14 A 60	60	85	100	150	4500	30,1	0,6	160	185	280	3
SKVA 20 B 130	140	180	220	190	6500	79,3	1,0	350	395	525	6
SKVA 14 A 150	150	200	270	150	4500	58,5	0,6	380	440	570	3
SKVA 14 A 250	250	325	420	150	4500	103	0,6	670	780	925	3
SKVA 20 B 250	250	325	420	190	6500	146,2	1,0	580	680	830	6
SKVA 20 B 275	280	364	470	190	6500	163	1,0	750	835	1025	6
SKVA 14 A 320	330	429	560	150	4500	137	0,6	800	930	1300	3
SKVA 14 A 420	420	546	710	150	4500	175	0,6	1000	1255	1600	3
SKVA 20 B 420	420	546	710	190	6500	224	1,0	1000	1255	1600	6
SKVA 20 B 460	460	598	780	190	6500	289	1,0	1240	1275	1650	6
SKVA 20 B 550	600	780	1000	190	6500	345	1,0	1590	1760	2100	6
<b>Plastic package, 1 varistor</b>											
SKVC 20 A 251	250	320	$390 \pm 15\%$	190	6500	140	$0,8^{5)}$	600	650	800	120
SKVC 20 A 460	460	615	$750 \pm 15\%$	190	6500	260	$0,8^{5)}$	1150	1270	1550	120
<b>Plastic package, 1 varistor + 1 capacitor 0,1 <math>\mu\text{F}</math></b>											
SKVC 20 A 460C	460	615	$750 \pm 15\%$	190	6500	260	$0,8^{5)}$	1150	1270	1550	130
<b>Plastic package, 3 varistors</b>											
SKVC 221	140	180	$220 \pm 15\%$	190	6500	70	$0,8^{5)}$	310	340	430	145
SKVC 391	250	320	$390 \pm 15\%$	190	6500	130	$0,8^{5)}$	590	630	790	145
SKVC 681	420	560	$680 \pm 15\%$	190	6500	155	$0,8^{5)}$	1000	1100	1300	145
SKVC 781	460	615	$750 \pm 15\%$	190	6500	170	$0,8^{5)}$	1100	1200	1500	145
SKVC 911	550	745	$910 \pm 15\%$	190	6500	210	$0,8^{5)}$	1350	1450	1900	145

<sup>1)</sup> IEC standard current pulse waveform  $8 \times 20\ \mu\text{s}$

<sup>2)</sup>  $10^4$  times during lifetime

<sup>3)</sup> Once during lifetime

<sup>4)</sup> Epoxy encapsulation carries Underwriter Laboratories flammability classification 94V-0

<sup>5)</sup>  $T_{case} \leq 85\text{ °C}$ . For higher values of  $P_{AV}$  see chapter B 4 last page.




Fig. 2 a Current / voltage characteristics (pulsed)




Fig. 2 b Current / voltage characteristics (pulsed)




Fig. 2 c Current / voltage characteristics (pulsed)




Fig. 2 d Current / voltage characteristics (pulsed)

# SKVA

Types	Dimensions			
	a max. mm	b max. mm	c max. mm	d mm
SKVA 14 A 42	16	19		
SKVA 14 A 60	16	19	4	2,2
SKVA 20 B 130	23	26		
SKVA 14 A 150	16	19	5	2,5
SKVA 14 A 250	17	20		3,3
SKVA 20 B 250	24	27		3,3
SKVA 20 B 275	24	27	6	3,6
SKVA 14 A 320	17	20		4,0
SKVA 14 A 420	17	20	7	4,6
SKVA 20 B 420	24	27	7	4,6
SKVA 20 B 460	24	27	7	5,0
SKVA 20 B 550	24	27	8	5,6

