High power cycling capability
Low on-state and switching losses
Designed for traction and industrial applications

Phase Control Thyristor
Type T953-800-65

Mean on-state current					I_{TAV}		800 A				
Repetitive peak off-state voltage					V_{DRM}		4600 ÷ 6500 V				
Repetitive peak reverse voltage					V_{RRM}						
Turn-off time					t_q		630, 800 µs				
V_{DRM}, V_{RRM}, V	4600	4800	5000	5200	5400	5600	5800	6000	6200	6400	6500
Voltage code	46	48	50	52	54	56	58	60	62	64	65
T_j, °C	-60 ÷ 125										

MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions	
ON-STATE					
I_{TAV}	Mean on-state current	A	800 838 685	T_c=73 °C, Double side cooled T_c=70 °C, Double side cooled T_c=85 °C, Double side cooled 180° half-sine wave; 50 Hz	
I_{TRMS}	RMS on-state current	A	1256	T_c=73 °C, Double side cooled 180° half-sine wave; 50 Hz	
I_{TSM}	Surge on-state current	kA	10.0 11.5	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=10 ms; single pulse; V_D=V_R=0 V; Gate pulse: I_G=2 A; t_{GP}=50 µs; di_G/dt≥1 A/µs
			10.5 12.0	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=8.3 ms; single pulse; V_D=V_R=0 V; Gate pulse: I_G=2 A; t_{GP}=50 µs; di_G/dt≥1 A/µs
I^2t	Safety factor	$A^2s \cdot 10^3$	500 660	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=10 ms; single pulse; V_D=V_R=0 V; Gate pulse: I_G=2 A; t_{GP}=50 µs; di_G/dt≥1 A/µs
			450 590	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=8.3 ms; single pulse; V_D=V_R=0 V; Gate pulse: I_G=2 A; t_{GP}=50 µs; di_G/dt≥1 A/µs
BLOCKING					
V_{DRM}, V_{RRM}	Repetitive peak off-state and Repetitive peak reverse voltages	V	4600÷6500	$T_{j\,min}$< T_j <$T_{j\,max}$; 180° half-sine wave; 50 Hz; Gate open	
V_{DSM}, V_{RSM}	Non-repetitive peak off-state and Non-repetitive peak reverse voltages	V	4700÷6600	$T_{j\,min}$< T_j <$T_{j\,max}$; 180° half-sine wave; single pulse; Gate open	
V_D, V_R	Direct off-state and Direct reverse voltages	V	0.6·V_{DRM} 0.6·V_{RRM}	T_j=$T_{j\,max}$; Gate open	

TRIGGERING				
I_{FGM}	Peak forward gate current	A	8	$T_j=T_{j\,max}$
V_{RGM}	Peak reverse gate voltage	V	5	
P_G	Gate power dissipation	W	4	$T_j=T_{j\,max}$ for DC gate current
SWITCHING				
$(di_T/dt)_{crit}$	Critical rate of rise of on-state current non-repetitive (f=1 Hz)	A/μs	60	$T_j=T_{j\,max}$; $V_D=0.67 \cdot V_{DRM}$; I_{TM}=1540 A; Gate pulse: I_G=2 A; t_{GP}=50 μs; $di_G/dt \geq 2$ A/μs
THERMAL				
T_{stg}	Storage temperature	°C	-60÷50	
T_j	Operating junction temperature	°C	-60÷125	
MECHANICAL				
F	Mounting force	kN	24.0÷28.0	
a	Acceleration	m/s^2	50	Device clamped

CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V_{TM}	Peak on-state voltage, max	V	2.40	T_j=25 °C; I_{TM}=1500 A	
$V_{T(TO)}$	On-state threshold voltage, max	V	1.269	$T_j=T_{j\,max}$; 0.5 π I_{TAV} < I_T < 1.5 π I_{TAV}	
r_T	On-state slope resistance, max	mΩ	0.981		
I_L	Latching current, max	mA	1500	T_j=25 °C; V_D=12 V; Gate pulse: I_G=2 A; t_{GP}=50 μs; $di_G/dt \geq 1$ A/μs	
I_H	Holding current, max	mA	300	T_j=25 °C; V_D=12 V; Gate open	
BLOCKING					
I_{DRM}, I_{RRM}	Repetitive peak off-state and Repetitive peak reverse currents, max	mA	200	$T_j=T_{j\,max}$; $V_D=V_{DRM}$; $V_R=V_{RRM}$	
$(dv_D/dt)_{crit}$	Critical rate of rise of off-state voltage[1)], min	V/μs	1000, 1600, 2000, 2500	$T_j=T_{j\,max}$; $V_D=0.67 \cdot V_{DRM}$; Gate open	
TRIGGERING					
V_{GT}	Gate trigger direct voltage, max	V	3.00 2.50 1.50	$T_j=T_{j\,min}$ T_j=25 °C $T_j=T_{j\,max}$	V_D=12 V; I_D=3 A; Direct gate current
I_{GT}	Gate trigger direct current, max	mA	500 300 150	$T_j=T_{j\,min}$ T_j= 25 °C $T_j=T_{j\,max}$	
V_{GD}	Gate non-trigger direct voltage, min	V	0.45	$T_j=T_{j\,max}$; $V_D=0.67 \cdot V_{DRM}$; Direct gate current	
I_{GD}	Gate non-trigger direct current, min	mA	55.00		
SWITCHING					
t_{gd}	Delay time, max	μs	3.00	T_j=25 °C; V_D=1500 V; $I_{TM}=I_{TAV}$; di/dt=200 A/μs; Gate pulse: I_G=2 A; V_G=20 V; t_{GP}=50 μs; di_G/dt=2 A/μs	
t_{gt}	Turn-on time, max	μs	14.00		
t_q	Turn-off time[2)], max	μs	630, 800	dv_D/dt=50 V/μs; $T_j=T_{j\,max}$; $I_{TM}=I_{TAV}$; di_R/dt=-10 A/μs; V_R=100V; $V_D=0.67 \cdot V_{DRM}$	
Q_{rr}	Total recovered charge, max	μC	4500	$T_j=T_{j\,max}$; I_{TM}=1000 A; di_R/dt=-5 A/μs; V_R=100 V	
t_{rr}	Reverse recovery time, typ	μs	60.0		
I_{rrM}	Peak reverse recovery current, max	A	150		

THERMAL					
R_{thjc}	Thermal resistance, junction to case, max	°C/W	0.020	Direct current	Double side cooled
R_{thjc-A}			0.044		Anode side cooled
R_{thjc-K}			0.036		Cathode side cooled
R_{thck}	Thermal resistance, case to heatsink, max	°C/W	0.004	Direct current	
MECHANICAL					
w	Weight, max	g	700		
D_s	Surface creepage distance	mm (inch)	39.55 (1.557)		
D_a	Air strike distance	mm (inch)	25.50 (1.004)		

PART NUMBERING GUIDE

T	953	800	65	A2	B2	N
1	2	3	4	5	6	7

1. Phase Control Thyristor
2. Design version
3. Mean on-state current, A
4. Voltage code
5. Critical rate of rise of off-state voltage, V/μs
6. Turn-off time (dv_D/dt=50 V/μs)
7. Ambient conditions: N – normal; T – tropical

NOTES

[1] Critical rate of rise of off-state voltage

Symbol of Group	A2	T1	P1	M1
$(dv_D/dt)_{crit}$, V/μs	1000	1600	2000	2500

[2] Turn-off time (dv_D/dt=50 V/μs)

Symbol of Group	C2	B2
t_q, μs	630	800

OVERALL DIMENSIONS

Package type: T.D4



All dimensions in millimeters (inches)

The information contained herein is confidential and protected by Copyright.
In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.



Fig 1 – On-state characteristics of Limit device

Analytical function for On-state characteristic:

$$V_T = A + B \cdot i_T + C \cdot \ln(i_T + 1) + D \cdot \sqrt{i_T}$$

	Coefficients for max curves	
	T_j = 25°C	$T_j = T_{j\,max}$
A	1.02290000	0.82252000
B	0.00073163	0.00099002
C	0.05070500	0.08275900
D	-0.00230610	-0.00438140

On-state characteristic model (see Fig. 1)



Fig 2 – Transient thermal impedance Z_{thjc} vs. time t

Analytical function for Transient thermal impedance junction to case Z_{thjc} for DC:

$$Z_{thjc} = \sum_{i=1}^{n} R_i \left(1 - e^{-\frac{t}{\tau_i}} \right)$$

Where ***i*** = 1 to ***n***, ***n*** is the number of terms in the series.

t = Duration of heating pulse in seconds.

$\mathbf{Z_{thjc}}$ = Thermal resistance at time t.

$\mathbf{R_i}$ = Amplitude of p_{th} term.

τ_i = Time constatnt of r_{th} term.

DC Double side cooled

i	1	2	3	4	5	6
$\mathbf{R_i}$, **K/W**	0.009168	0.002899	0.001522	0.006297	0.00003033	0.00008163
τ_i, **s**	0.9681	0.05144	0.002417	0.07706	0.0004122	0.0002166

DC Anode side cooled

i	1	2	3	4	5	6
$\mathbf{R_i}$, **K/W**	0.02398	0.009274	0.009094	-0.00003741	0.00155	0.0001282
τ_i, **s**	9.752	1.065	0.06762	0.01374	0.002533	0.0002841

DC Cathode side cooled

i	1	2	3	4	5	6
$\mathbf{R_i}$, **K/W**	0.01568	0.00922	0.009098	0.00006319	0.001526	0.000116
τ_i, **s**	9.755	1.039	0.06857	0.01397	0.002449	0.0002632

Transient thermal impedance junction to case Z_{thjc} model (see Fig. 2)



Fig 3 – Maximum recovered charge Q_{rr-i} (integral) vs. commutation rate di_R/dt



Fig 4 – Maximum recovered charge Q_{rr} vs. commutation rate di_R/dt (25% chord)



Fig 5 – Maximum reverse recovery current I_{rrM} vs. commutation rate di_R/dt



Fig 6 – Maximum recovery time t_{rr} vs. commutation rate di_R/dt (25% chord)



Fig. 7 - Mean on-state power dissipation P_{TAV} vs. mean on-state current I_{TAV} for sinusoidal current waveforms at different conduction angles (f=50Hz, DSC)



Fig. 8 – Mean on-state power dissipation P_{TAV} vs. mean on-state current I_{TAV} for rectangular current waveforms at different conduction angles and for DC (f=50Hz, DSC)



Fig. 9 – Mean on-state current I_{TAV} vs. case temperature T_C for sinusoidal current waveforms at different conduction angles (f=50Hz, DSC)



Fig. 10 - Mean on-state current I_{TAV} vs. case temperature T_C for rectangular current waveforms at different conduction angles and for DC (f=50Hz, DSC)



Fig. 11 – Maximum surge on-state current I_{TSM} and safety factor I^2t vs. pulse length t_p



Fig. 12 - Maximum surge on-state current I_{TSM} vs. number of pulses n_p