



STB THREE

PHASES INDIVIDUAL CONTROL Series

COMPENSATED POWER VOLTAGE REGULATOR



STB-33-800KVA



OUTLINE & PACKING

MODEL	STB-33-800KVA
OUTPUT POWER(KVA)	800
OUTLINE(CM)	2000*1420*1350
NET WEIGHT(KG)	1800

SPECIFICATIONS:

INPUT VOLTAGE	Three phase:304V-456V / 323V-437V Single phase:176V-264V / 187V-253V
OUTPUT VOLTAGE	Single phase :220V Three phases :380V
OUTPUT DEVIANCE	1-5% Adjustable
FREQUENCY	50HZ~60HZ
EFFICIENCY	≥95%
RESPONSE TIME	≤1.5S
AMBIENT TEMPERATURE	-10℃~+40℃
INSULATION RESISTANCE	≥5MΩ
OVERLOAD	DOUBLE RETED CURRENT,ONE MIN
WAVEFORM DISTORTION	NON-LACK FIDELITY WAREFORM
PROTECT	OVERTENSION、OVERCURRENT、LACK PHASES





Technical Parameters

1	Type	STB-33
2	Capacity	800KVA
3	Input voltage	Circuit breaker
		1000A
		Phase
		Three Phase
4	Output voltage	Voltage
		304-456v (L1+L2+L3+N)
		Frequency
		50/60Hz
5	Rated output current	972A
6	Voltage Accuracy	±1-5% V Adjustable(Factory set±2%)
7	Control principle	Independent regulation for three phase
8	Certificates	CE,ROHS,SGS,ISO,CQC
9	Display	LCD touch screen
10	Response time	<10ms
11	Heat Efficiency	≥98%(on full load)
12	Insulation strength	2500V/Min
13	Insulation Class	H class (200 degree C)
14	Wave form Distortion	No distortion (Nil)
15	Connection method	Star/Star
16	Cooling method	Air cooling/ Fan system cooling
17	Resist electric strength	2500VAC/min
18	Noise	≤30db (exclude forced air cooling system)
19	Temperature Rise	≤75°C
20	cabinet	IP20
21	Environment	Ambient
		-20~55°C
		Related
		10~90%
		Altitude
22	dimension (mm)	2200(H)*1420(W)*1350(D)
23	weight (kgs)	1800
24	Warranty	12 months
25.Protection Function	Over/under voltage protection	When the input voltage exceeds the value of over/under voltage, the stabilizer will protect
	Over current	When the current exceeds the rated value, automatically cut off the input
	Overload and short circuit protection	When the load exceeds the overload value or short circuit of the equipment, it can cut off the power supply within the specified time;
	Position Limitation Protection	When the brush is running over the area, automatically stop adjustment;
	Bypass function	manual bypass, when the voltage stabilizer needs maintenance or in failure, the switch can be manual controlled
	Effective sampling circuit control	High accuracy, good sensitivity, frequency characteristic measurement, good rate, high input impedance, low output impedance, wide range and low power consumption power supply
	Circuit Function	When the sampling voltage is lower than the lower reference voltage or higher than the upper limit voltage, the brush will automatically return to the center;
	Temperature protection	Three phase Over temperature protection protection
	Warning	With alarm